

KEL-B

MOULDED RESPIRATORS



Packing: 20 masks per box

Complies with EN:149:2001 +A1:2009 FFP2 NR

NRCS/8072/0107

- **Low breathing resistance for increased wearer comfort**
- **Heavy duty, tab mounted, head straps**
- **Colour coded plastic adjustable nose clip**
- **Soft foam nosepiece for comfort and custom fit**
- **PP inner with no loose fibre**

TECHNICAL INFORMATION	K003
CE EN 149-2001+A1:2009	FFP2NR
OEL – Occupational Exposure Limit	4.5
APF – Assigned Protection Factor	4
NPF – Nominal Protection Factor	4.5
NOSE BRIDGE ADJUSTER COLOUR	YELLOW
Total Inward Leakage (%)	<22%
Penetration (%)	<20%
Carbon dioxide content of inhalation air (%)	<1%
Inhalation resistance 30 l/min (mbar)	<0.6mbar
Inhalation resistance 95 l/min (mbar)	<2.1mbar
Exhalation resistance 160 l/min (mbar)	<3.0mbar

Meets the requirement of the Personal Protective Equipment directive, 89/686/EEC
Controlled by: BSI (CE 0086)
Tested with particles between 0.2um – 2.0um

USER GUIDE	K003– FFP2NR
ARSENIC	
ASBESTOS FIBRES	
CADMIC	
CEMENT	•
CHROMIUM	
GLASS	•
IRON FUMES	
IRON & STEEL MINING	•
LEAD	
NICKEL	
OILS	•
SILICA	•
SULPHURIC ACID MIST	
TEXTILES	•
WELDING VAPOURS	

WOOD	•
ZINC FUMES	

This user guide is a brief outline to direct the user to the appropriate mask. This guide should not be used as the only means of respirator selection. The fit, work conditions and contaminants present should be considered with the exposure time to determine the correct mask. Disposable masks should not be used when oxygen concentrations are less than 19% or the work area has unknown contaminants that could cause immediate danger to the life and health of the user.